



NOTES:

1. COPPER PLATE TO A THICKNESS OF 0.005'(0.002)
TIN PLATE TO A THICKNESS OF 0.008(.0032)
2. 2° DRAFT RUNNING FROM P/L. TO REDUCE MASS .EXCEPT AS NOTED.
3. ALL CORNERS AND FILLETS UP TO 0.38R(.015R)MAX .EXCEPT AS NOTED.
4. DEMENSIONS APPLY AT PARTING LINE OF POINT NEAREST TO IT .EXCEPT AS NOTED.
5. ALL BURRS AND SHARP EDGES SHALL BE REMOVED.
6. DIMENSIONS APPLY AFTER PLATING
7. GATE VESTIGE (2X) MUST NOT VIOLATE MAX O.D.
8. PART SHALL MEET SOLDERABILITY REQUIREMENTS OF SA SPEC 499402
9. DIMENSION IN PARENTHESSES IN INCHS
10. MATERIAL: ZINC#3.

| | | | | | |
|---|----------|---|------|-----------------|--------|
| NO. | | DESCRIPTION | Q'TY | MATERIAL | PLATED |
|  | |  | | | |
| 圖名 NAME | GSK-146M | | | | |
| 圖號 DWG NO | | | | | |
| 單位 UNIT | MM | 一般公差 | ±0.2 | 繪圖 DRAW. BY | AXL |
| 比例 SCALE | NONE | .X | ±0.1 | 校對 CHECKED | |
| SHEET | 1/1 | .XX | | 審核 APPVL. BY | |
| | | .XXX | | | |
| | | ANGLES | | | |

| | | | | |
|-----|---------------|----------|------|---------|
| [A] | ISSUED | 9/13/07' | AXL | |
| REV | DESCRIPTION | DATE | NAME | ECN NO. |