



PCB LAYOUT
TOLERANCE: ± 0.05 mm

ORDER INFORMATION

SMT TYPE **S RJ45-T 01 A 0 S6**

SELECTIVE PLATING (FOR STAMPING CONTACT)
 S1=GOLD FLASH PLATING
 S2=GOLD 5u" PLATING
 S3=GOLD 10u" PLATING
 S4=GOLD 15u" PLATING
 S5=GOLD 30u" PLATING
 S6=GOLD 50u" PLATING

Led Configuration:
 0: WITHOUT LED

TOOLING FAMILY

NUMBER OF PORTS

Mounting Type
 T= R/A TAB UP
 RJ45 SERIES

NOTES:

- MATERIAL:**
 HOUSING: DSM STANYL TE250F6 (NYLON-46)
 HEAT DEFLECTION TEMP. 290°C, BLACK COLOR, UL94V-0.
 CONTACTS: 0.35mm THICK PHOS. BRONZE PLATED WITH HARD GOLD AND GOLD FLASH IN SOLDER AREA.
 OVER ENTIRE PIN WITH 50 u" NICKEL UNDER PLATED.
 RoHS COMPLIANT SOLDER ON SOLDER TAILS.
 SHIELD: 0.25mm THICK COPPER ALLOY, PLATED WITH NICKEL.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.
- RoHS COMPLIANT.

TOLERANCE	
LINEAR	ANGLES
X. ±	X° ±
.X ± 0.25	.X° ±
.XX ± 0.20	.XX° ±
.XXX ± 0.10	.XXX° ±



TITLE: RJ45 SINGLE PORT W/ SHIELD SMT TYPE			
PART NO.	SRJ45-T01A0S6		
DWG NO.	GTI08-30152		
UNITS	SCALE	SHEET	REV
MM	NONE	1 OF 1	A

A	ISSUED	AXL	4/25/08
REV	ECN NO.	NAME	DATE

APPD:	MAT'L:
CHKD:	FINISH:
DRWN: AXL	Q'TY:

