



P.C.B LAYOUT

Electrical Characteristics :

- Insulation Resistance : 500M Ω Min.
- Contact Resistance : 30m Ω Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.5A

Mechanical:

Housing : PBT With Glass Fiber UL94V-0
 Contact : Selective Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

Ordering Information:

RJ XX-T 02 A XX

- Plating: (Round shape Contact)
- P1 = Gold Flash
- P2 = 5u"
- P3 = 10u"
- P4 = 15u"
- P5 = 30u"
- P6 = 50u"
- Tooling Family
- Number of Ports
- Mounting Type:
- T = R/A tab up
- D = R/A tab down
- U = Multiple ports Stacked two rows
- RJ Series:
- 11 = 6Px2C
- 14 = 6Px4C
- 25 = 6Px6C

For Multiple Ports with Multiple Series Please Contact Manufacture for More Information

RoHs Compliant

[E]	Part Number Change	SWL	4/29/08'	TOLERANCE	
[D]	ADD PORT 1, 2 OPTION	Kevin	1/23/08'	LINEAR	ANGLES
[C]	REVISE COLOR CODE	AXL	7/28/06'	X.±	X'.±
[B]	ADD DIMENSIONS	AXL	7/18/06'	.X±0.25	.X'±
[A]	ISSUED	AXL	4/20/06'	.XX±0.15	.XX'±
REV	ECN NO.	NAME	DATE	.XXX±0.05	.XXX'±



TITLE:		6P6C SIDE ENTRY PCB JACK 2 PORTS			
PART NO.		RJ25-T02AXX			
DWG NO.		SC-10313			
UNITS	SCALE	SHEET	REV	APPD:	
				MAT'L:	
MM	NONE	1 OF 1	E	CHKD:	
				FINISH:	
DRWN: AXL		Q'TY:		[Symbol]	